

(ALL SERVICES LARGER THAN 200 AMPS ARE OWNED AND MAINTAINED BY THE CUSTOMER) NOTES - SERVICES 200 AMP OR LESS:

- 1. METER SHALL BE IN DIRECT LINE-OF-SIGHT WITH THE UTILITY SECONDARY VOLTAGE JUNCTION BOX/J-BOX. 2. METER SHALL BE LOCATED IN THE NEAREST 1/4 OF THE STRUCTURE TO THE SOURCE; NOT FENCED IN.
 3. ALL SERVICES 200 AMP OR LESS REQUIRE A LEVER BYPASS METER BASE.
 4. ALL ELECTRIC CONDUIT TO BE 2" SCH/40 PVC WITH 24" RADIUS SWEEPS.
 5. MICRODUCT CONDUIT (PROVIDED BY LPC) SHALL BE INSTALLED IN THE ELECTRIC TRENCH BY THE BUILDER.

- 6. THE MICRODUCT SHALL EXTEND 6" ABOVE GRADE AT THE SERVICE ENTRANCE, TIE WRAPPED TO THE ELECTRIC SERVICE CONDUIT AND LAND INSIDE OF THE UTILITY J-BOX LABELED "BROADBAND" ON LID
- 7. METER HOUSING AND ONE PIPE STRAP SHALL BE ATTACHED WITH AN APPROPRIATE ANCHORING METHOD SO AS NOT TO BECOME DETACHED OVER TIME.
- 8. METER HOUSING AND CONDUIT SHALL NOT BE ENCLOSED WITHIN ANY STRUCTURES' SIDING OR OTHER MATERIALS AND MUST REMAIN ACCESSIBLE FOR FUTURE MAINTENANCE.
- 9. USE PVC SLIDER OR EXPANSION COUPLING AT THE ENTRANCE TO THE METER HOUSING.
- 10. SERVICE LATERAL CONDUCTORS SHALL BE CUT TO A LENGTH THAT ALLOWS THEM TO EXTEND 30" ABOVE THE J-BOX LID OR 48" ABOVE THE TRANSFORMER VAULT AND COILED WITHIN
- 11. CALL 1-800-922-1987 OR 811 TO OBTAIN UTILITY LOCATES.

METERING SINGLE FAMILY N.T.S.



Print Date: 7/24/2019		011011011	DETAIL
File: 2019 SDT TEMPLATE.cel	CIIY of L	ONGMONI	
REVISION BY: NOTEBOOMJ		707.054.0700	700-16
SCALE: NOT TO SCALE	1100 S SHERMAN ST Longmont, CO 80501	Phone: 303-651-8386 FAX: 303-651-8796	, 55 15